

View Online at <https://aerobasegroup.com/nsn/5930-01-155-1252>

**Thread Class:**

2b single mounting facility

**Thread Length:**

0.250 inches 1st mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.080 inches

**Overall Height:**

2.500 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.300 inches single actuator

**Individual Section Quantity:**

2

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

A

**Longest Horizontal Distance Between Mounting Centers:**

1.640 inches 2nd mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.640 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

4 each section rear

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Rotor Through Connection Quantity:**

1 each section

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round single actuator

**Criticality Code Justification:**

Zzzy

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo3283

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0