NSN 5930-01-155-1252

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-1252 **Thread Class:** 2b single mounting facility **Thread Length:** 0.250 inches 1st mounting facility **Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 3.080 inches **Overall Height:** 2.500 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.300 inches single actuator **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Knob Manufacturer Part Number: Longest Horizontal Distance Between Mounting Centers:** 1.640 inches 2nd mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.640 inches 2nd mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 4 each section rear **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility

125.0 ac at sea level

Rotor Through Connection Quantity:

Contact Voltage Rating In Volts:

1 each section

NSN 5930-01-155-1252Rotary Switch - Page 2 of 2



Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round single actuator
Criticality Code Justification:
Zzzy
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Special Features:
tem must comply with requirements of defense supply center columbus production standard no. Lo3283
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Reference Number Differentiating Characteristics:
Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing
and testing specifications available at the dla icp
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A052b0