

View Online at <https://aerobasegroup.com/nsn/5930-01-155-1262>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

1.000 inches

Body Length:

1.250 inches

Body Height:

0.875 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.125 inches

Actuator Free Position Height:

0.563 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Kurz and root co generator model 4

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

17.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.028 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 7.000 amperes inductive dc and 10.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

8 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0