NSN 5930-01-155-1262

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-1262

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
1.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Overall Height:
1.000 inches
Body Length:
1.250 inches
Body Height:
0.875 inches
Unthreaded Mounting Hole Diameter:
0.114 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.125 inches
Actuator Free Position Height:
0.563 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
End Application:
Kurz and root co generator model 4
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
17.0 ounces
Actuator Movement:
Between 0.060 pretravel inches and 0.015 overtravel inches and 0.028 differential inches

10.000 amperes resistive dc and 7.000 amperes inductive dc and 10.000 amperes resistive ac

Contact Load Current Rating At Maximum Rated Voltage:

NSN 5930-01-155-1262 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
8 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0