

View Online at <https://aerobasegroup.com/nsn/5930-01-155-1263>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.279 inches and 0.283 inches

**Body Length:**

0.510 inches

**Body Width:**

Between 0.151 inches and 0.156 inches

**Body Height:**

0.350 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.093 inches

**Actuator Height:**

0.065 inches

**Actuator Free Position Height:**

0.355 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Actuating Force:**

8.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.050 pretravel inches and 0.004 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc

**Precious Material And Location:**

Terminals gold and contacts gold

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 printed circuit

**Specification Data:**

81349-mil-s-8805/101 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0