## NSN 5930-01-155-1277

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-1277

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
0.750 inches
Overall Height:
2.751 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.090 inches
Actuator Width:
0.620 inches
Actuator Color:
Red single actuator and red single actuator
Illuminated Actuator Color:
Red single actuator and red single actuator
Actuator Inscription:
Manual keying transmit single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Sounding set, sonar an/bqn-17
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-155-1277

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Horizontal split lens

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

5 tab, solder lug and 6 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0