## NSN 5930-01-155-1279

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-1279

## Body Style:

Panel mount

## Hazardous Locations/environmental Protection:

Explosion proof

## **Overall Length:**

0.750 inches

## **Overall Height:**

2.620 inches

### **Overall Width:**

0.750 inches

**Body Length:** 

## 0.688 inches

Body Width:

#### 0.750 inches

Case Material:

#### Metal

### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

Sounding set, sonar an/bqn-17

## Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

## Features Provided:

Rfi shielding

## Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

#### **Special Features:**

Five lamp terminals provided

#### **Precious Material And Location:**

Contacts silver

## **Terminal Type And Quantity:**

9 turret and 5 tab, solder lug

## Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

No

# NSN 5930-01-155-1279

Push Switch - Page 2 of 2

Fiig: A053a0

