NSN 5930-01-155-1280



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-155-1280 **Body Style:** Panel mount **Hazardous Locations/environmental Protection:** Explosion proof **Overall Length:** 0.750 inches **Overall Height:** 2.620 inches **Overall Width:** 0.750 inches **Body Length:** 0.688 inches **Body Width:** 0.750 inches **Case Material:** Metal **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **End Application:** Sounding set, sonar an/bqn-17 Inclosure Type: Fully enclosed **Mounting Method:** Panel **Features Provided:** Rfi shielding **Nonpile-up Contact Arrangement:** 4 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac **Special Features:**

Five lamp terminals provided

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5930-01-155-1280

Push Switch - Page 2 of 2



Fiig:

A053a0