NSN 5930-01-155-5382

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-5382

| Body Style: |
|---|
| Hole mounted |
| Overall Length: |
| 7.025 inches |
| Overall Height: |
| 3.190 inches |
| Overall Width: |
| 2.120 inches |
| Actuator Length: |
| 2.000 inches |
| Actuator Style: |
| Roller arm |
| Actuator Roller Diameter: |
| 0.875 inches |
| Housing Height: |
| 2.160 inches |
| Housing Length: |
| 6.000 inches |
| Housing Width: |
| 2.120 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 3.375 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width: |
| 1.500 inches |
| Maximum Voltage Rating In Volts: |
| 600.0 ac and 230.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| 48.0 ounces |
| Actuator Movement: |
| Between 12.0 pretravel degrees and 60.0 overtravel degrees and 5.0 differential degrees |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 250.000 milliamperes resistive dc and 1.500 amperes resistive ac |

3 screw

Terminal Type And Quantity:

NSN 5930-01-155-5382

Sensitive Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0