NSN 5930-01-155-5553

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-5553

Overall Length:
4.938 inches
Overall Height:
5.250 inches
Overall Width:
2.875 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes resistive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+10.00/+180.00 actuation point pounds per square inch gage and +10.00/+180.00 deactuation point pounds per square inch gage
Contact Adjustment Type:

External deactuation point screw and external actuation point screw

NSN 5930-01-155-5553

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 550.0 dc at sea level third voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator: Rectangular Thread Series Designator: Unf single pressure connection Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0