NSN 5930-01-155-6282

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-6282

Body Style:				
Panel mount				
Hazardous Locations/environmental Protection:				
Explosion proof				
Overall Length:				
0.750 inches				
Overall Height:				
2.751 inches				
Overall Width:				
0.750 inches				
Body Length:				
0.688 inches				
Body Width:				
0.750 inches				
Case Material:				
Metal				
Actuator Length:				
0.620 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.090 inches				
Actuator Width:				
0.620 inches				
Actuator Color:				
Red single actuator				
Illuminated Actuator Color:				
Red single actuator				
Actuator Inscription:				
Event mark single actuator				
Maximum Voltage Rating In Volts:				
115.0 ac and 28.0 dc				
End Application:				
Sounding set, sonar an/bqn-17				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Panel				
Features Provided:				
Rfi shielding				
Nonpile-up Contact Arrangement:				

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-155-6282

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

D۳	acione	Matoria	I And	Location:
71	ecious	wateria	II Ana	Location.

Contacts silver

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0