NSN 5930-01-155-6509

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-6509

Overall Length:
5.188 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Capillary Tube Length:
132.0 inches
Bulb Length:
3.625 inches
Bulb Diameter:
0.688 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Mounting Method:
Mounting Method: Bracket and unthreaded hole
Mounting Method: Bracket and unthreaded hole Features Provided:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 9.6 amperes inductive load fourth voltage
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 9.6 amperes inductive load fourth voltage Contact Adjustability:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 9.6 amperes inductive load fourth voltage Contact Adjustability: Deactuation point not adjustable, manual reset and actuation point adjustable

Contact Adjustment Type:

External actuation point screw

NSN 5930-01-155-6509

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts: 550.0 dc at sea level third voltage Media For Which Designed: Gas or liquid Precious Material And Location: Contacts silver Precious Material: Silver Style Designator: Rectangular Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0