

View Online at <https://aerobasegroup.com/nsn/5930-01-155-7022>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Case Material:**

Metal

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.218 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.190 inches

**Housing Height:**

Between 1.720 inches and 1.780 inches

**Housing Length:**

2.460 inches

**Housing Width:**

1.000 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.625 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 250.0 dc

**End Application:**

4920-01-039-4139

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 9.0 ounces and 13.0 ounces

**Actuator Movement:**

Between 0.015 pretravel inches and 0.141 overtravel inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 2.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0