

View Online at <https://aerobasegroup.com/nsn/5930-01-155-7764>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Fungus resistant

Overall Length:

3.437 inches

Overall Height:

1.376 inches

Overall Width:

0.750 inches

Bushing Length:

0.281 inches

Body Length:

2.125 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Actuator Style:

Round

Actuator Diameter:

0.375 inches

Actuator Height:

0.875 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

110.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contacts palladium and leaf springs silver

Thread Series Designator:

Unef

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0