## NSN 5930-01-155-7764

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-7764

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Fungus resistant
Overall Length:
3.437 inches
Overall Height:
1.376 inches
Overall Width:
0.750 inches
Bushing Length:
0.281 inches
Body Length:
2.125 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Style:
Round
Actuator Diameter:
0.375 inches
Actuator Height:
0.875 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained and center position maintained
Actuator Position-locking Relationship:
Up position no locking action and down position no locking action and center position locked in
Maximum Voltage Rating In Volts:
110.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.375 inches
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit

1.000 amperes resistive dc and 3.000 amperes resistive ac

**Contact Load Current Rating At Maximum Rated Voltage:** 

## NSN 5930-01-155-7764

Lever Switch - Page 2 of 2



Preci	ous	Materi	ial A	\nd	Locati	on:

Contacts palladium and leaf springs silver

**Thread Series Designator:** 

Unef

**Terminal Type And Quantity:** 

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0