# NSN 5930-01-155-8520

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-8520

Hazardous Locations/environmental Protection:	Hazardous	Locations/environmental Protection:	
-----------------------------------------------	-----------	-------------------------------------	--

Corrosion resistant

**Overall Length:** 

2.881 inches

# **Overall Height:**

1.000 inches

# Overall Width:

1.000 inches

# Body Diameter:

1.000 inches

# **Bushing Length:**

0.657 inches

# Body Length:

1.100 inches

# Case Material:

Metal

### Actuator Style:

Roller plunger

## Actuator Free Position Height:

1.781 inches

## Actuator Roller Diameter:

0.500 inches

### Actuator Roller Width:

0.120 inches

## Maximum Voltage Rating In Volts:

28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Threaded bushing

#### Thread Size:

0.625 inches

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

64.0 ounces

### Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

## **Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc

# NSN 5930-01-155-8520

Sensitive Switch - Page 2 of 2

**Thread Series Designator:** 

Unef

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

