NSN 5930-01-155-8725

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-8725

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight
Overall Length:
5.453 inches
Overall Height:
1.844 inches
Overall Width:
1.625 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
2.344 inches
Actuator Roller Diameter:
0.500 inches
Housing Height:
1.844 inches
Housing Length:
4.547 inches
Housing Width:
1.625 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
240.0 ac and 250.0 dc
End Application:
4920-01-096-3932
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, both positions maintained single switch unit
Switch Actuating Force:
48.2 ounces
And the Manager of

Actuator Movement:

0.057 pretravel inches and 0.236 overtravel inches and 0.028 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contacts silver

NSN 5930-01-155-8725

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity	:
----------------------------	---

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0