NSN 5930-01-155-9286

Thermostatic Switch - Page 1 of 2

Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage

Overall Length: 1.250 inches



View Online at https://aerobasegroup.com/nsn/5930-01-155-9286

Overall Height:
0.413 inches
Overall Width:
0.401 inches
Body Length:
0.776 inches
Body Width:
0.401 inches
Body Height:
0.251 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Mounting Facility Centers:
1.000 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
2.5 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
-20.00/+200.00 actuation point degrees fahrenheit and -20.00/+200.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:
5.00 differential point degrees fahrenheit and 149.00 actuation point degrees fahrenheit and 144.00 deactuation point degrees fahrenheit

NSN 5930-01-155-9286

Thermostatic Switch - Page 2 of 2



Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas or liquid

Style Designator:Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A048b0