# NSN 5930-01-155-9880

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-9880

# **Thread Class:**

2b single mounting facility

# **Overall Length:**

2.563 inches

# **Overall Height:**

1.750 inches

# **Overall Width:**

1.750 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.938 inches single actuator

#### Individual Section Quantity:

1

#### Longest Horizontal Distance Between Mounting Centers:

1.375 inches single mounting facility

# Switch Contact Basic Design:

Nonpile-up symmetrical

# **Pole Quantity:**

1 single section rear

# Throw Quantity:

32 single section rear

#### **Mounting Method:**

Threaded hole single mounting facility

# Thready Qty Per Inch (tpi):

32 single mounting facility

# Thread Size:

0.138 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

120.0 ac at sea level

#### **Mounting Facility Pattern:**

Two position in-line single mounting facility

#### Switch Actuator Indexing Position Quantity:

32 single actuator

# Shaft Type:

Round single actuator

#### **Terminal Type:**

Turret

## **Contact Switching Action:**

Makes before breaks single section rear

# Switch Actuator Positioning Increment:

11.25 degrees single actuator

# NSN 5930-01-155-9880

Rotary Switch - Page 2 of 2



# Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

15.0 amperes resistive load ac at sea level

# **Precious Material And Location:**

Contacts and wipers silver

**Precious Material:** 

Silver

# Style Designator:

Tap, square frame

# Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A052b0