# NSN 5930-01-155-9884

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-9884

#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Explosion proof

## **Overall Length:**

0.750 inches

#### **Overall Height:**

2.710 inches

#### **Overall Width:**

0.750 inches

#### **Body Length:**

0.688 inches

#### **Body Width:**

0.750 inches

#### Case Material:

Metal

## Actuator Length:

0.620 inches

## Actuator Style:

Rectangular

## Actuator Height:

0.090 inches

#### Actuator Width:

0.620 inches

#### Actuator Color:

Green single actuator and red single actuator

#### **Illuminated Actuator Color:**

Green single actuator and red single actuator

#### **Actuator Inscription:**

Vacm vacm single actuator

#### Actuator Color Sequence:

Upper half of actuator green lower half of actuator red

#### Maximum Voltage Rating In Volts:

28.0 dc

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

## **Features Provided:**

Rfi shielding

## Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-155-9884

Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

#### **Precious Material And Location:**

Contacts gold

## Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

#### Fiig:

A053a0