NSN 5930-01-155-9887

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-155-9887

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
0.750 inches
Overall Height:
2.751 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.090 inches
Actuator Width:
0.620 inches
Actuator Color:
Green single actuator and red single actuator
Illuminated Actuator Color:
Green single actuator and red single actuator
Actuator Inscription:
Cmptr cmptr single actuator
Actuator Color Sequence:
Upper half of actuator green lower half of actuator red
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-155-9887

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0