

View Online at <https://aerobasegroup.com/nsn/5930-01-155-9897>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture proof and corrosion resistant

Bushing Length:

0.300 inches

Body Length:

0.560 inches

Actuator Style:

Round

Actuator Diameter:

0.375 inches

Actuator Height:

0.281 inches

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

End Application:

1190-01-084-3147

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action, with contact on arm single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 15.000 amperes inductive ac and 3.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0