NSN 5930-01-156-5584

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-156-5584

View Online at https://aerobasegroup.com/nsn/5930-01-156-5584
Thread Class:
2a
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
2.040 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Diameter:
0.750 inches
Bushing Length:
0.440 inches
Body Length:
0.950 inches
Actuator Height:
0.400 inches
Maximum Voltage Rating In Volts:
115.0 ac and 30.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, single throw, normally open, double make, momentary action 1st switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:

N/a

NSN 5930-01-156-5584

Push Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A053a0