## NSN 5930-01-156-5718

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-156-5718

| Body Style:   |
|---|
| Panel mounted   |
| Overall Length:   |
| 3.047 inches  |
| Overall Height:   |
| 0.870 inches  |
| Overall Width:  |
| 0.870 inches  |
| Body Length:  |
| 2.750 inches  |
| Body Width:   |
| 0.870 inches  |
| Body Height:  |
| 0.870 inches  |
| Case Material:  |
| Metal   |
| Actuator Length:  |
| 0.730 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.297 inches  |
| Actuator Width:   |
| 0.730 inches  |
| Actuator Color:   |
| White single actuator and amber single actuator           |
| Illuminated Actuator Color:                               |
| White single actuator and amber single actuator           |
| Actuator Inscription:                                     |
| Normal stdoff single actuator                             |
| Illuminated Actuator Color Sequence:                      |
| Upper half of actuator white lower half of actuator amber |
| Maximum Voltage Rating In Volts:                          |
| 230.0 ac and 28.0 dc                                      |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Panel   |
| Footunes Brandalad  |

**Features Provided:** 

Rfi shielding and full display lens

**Nonpile-up Contact Arrangement:** 

2 pole, double throw, both positions maintained single switch unit

## NSN 5930-01-156-5718

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac

**Precious Material And Location:** 

Contacts gold

**Terminal Type And Quantity:** 

6 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0