

View Online at <https://aerobasegroup.com/nsn/5930-01-156-5937>

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

Between 2.590 inches and 2.650 inches

**Overall Height:**

2.235 inches

**Overall Width:**

2.020 inches

**Unthreaded Mounting Hole Diameter:**

0.160 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.132 inches single mounting facility and 2.152 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.190 inches single mounting facility and 1.210 inches single mounting facility

**End Application:**

Sonar signal processing set an/sqr-17

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel single actuator

**Features Provided:**

Metallic inclosure and rfi shielding

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

1/17, 2/18, 3/19, 4/20, 5/21, 6/22, 7/23, 8/24, 9/25, 10/26, 11/27, 12/28, 13/29, 14/30, 15/31, 16/32 single section

**Contact Arrangement Truth Table:**

Binary with common not-true bits, 2 pole - 16 positions single section

**Color:**

White single indicator marking

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0