## NSN 5930-01-156-7006

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-156-7006

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.250 inches single mounting facility

**Overall Length:** 

Between 1.845 inches and 1.905 inches

**Overall Height:** 

Between 1.720 inches and 1.780 inches

**Overall Width:** 

Between 1.345 inches and 1.405 inches

First Flat Length:

0.406 inches single actuator

Flat Height:

0.183 inches single actuator

**Shaft Length:** 

0.500 inches single actuator

**End Application:** 

Automatic washer model ca3410

**Mounting Method:** 

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.625 inches single mounting facility

**Contact Voltage Rating In Volts:** 

250.0 highest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Quick disconnect, male

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

7.5 amperes resistive load highest ac voltage rating at sea level

**Style Designator:** 

Tap, square frame

**Thread Series Designator:** 

Un single mounting facility

## NSN 5930-01-156-7006

Rotary Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0