

View Online at <https://aerobasegroup.com/nsn/5930-01-156-7255>

Body Style:

Printed circuit

Overall Length:

0.700 inches

Overall Height:

0.480 inches

Overall Width:

Between 0.360 inches and 0.400 inches

Body Length:

0.700 inches

Body Width:

Between 0.360 inches and 0.400 inches

Body Height:

Between 0.240 inches and 0.300 inches

Case Material:

Plastic

Switch Actuator Quantity:

6

Actuator Style:

Rectangular

Actuator Height:

Between 0.195 inches and 0.205 inches

Actuator Width:

0.070 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

6.0 dc and 24.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Printed circuit

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained 6th switch unit

Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes resistive dc and 25.0 milliamperes resistive dc

Precious Material And Location:

Contact surfaces gold

Test Data Document:

81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 printed circuit

Specification Data:

81349-mil-s-83504/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0