

View Online at <https://aerobasegroup.com/nsn/5930-01-156-7835>

Thread Class:

2a

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.201 inches

Switch Actuator Quantity:

1

Actuator Length:

0.312 inches

Actuator Style:

Rectangular

Actuator Height:

0.643 inches

Actuator Width:

0.312 inches

Actuator Free Position Height:

1.205 inches

Housing Height:

1.780 inches

Housing Length:

3.790 inches

Housing Width:

1.540 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.340 inches

Maximum Voltage Rating In Volts:

120.0 ac

End Application:

E.M.D. Models gmeqr8645e6 and gmeql8645e6 diesel engines aboard 180 ft class coast guard vessels

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thread Size:

0.190 inches

Switch Release Force:

8.0 ounces

Switch Actuating Force:

64.0 ounces

Actuator Movement:

0.065 pretravel inches and 0.235 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Thread Series Designator:

Unf

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0