NSN 5930-01-157-2732

Thermostatic Switch - Page 1 of 2



The model and of the first age in the fi
View Online at https://aerobasegroup.com/nsn/5930-01-157-2732
Thread Class:
2b all threaded hole
Overall Length:
1.656 inches
Overall Height:
2.578 inches
Overall Width:
2.359 inches
Body Height:
2.422 inches
Distance Between Mounting Facility Centers:
1.750 inches
Capillary Tube Length:
24.0 inches
Bulb Length:
12.250 inches
Bulb Diameter:
0.188 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket and threaded hole
Features Provided:
Capillary tube end seal connection
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.138 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab solder lug

Contact Load Current Rating:

181.0 milliamperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.00/+700.00 actuation point degrees fahrenheit and +0.00/+700.00 deactuation point degrees fahrenheit

NSN 5930-01-157-2732

Thermostatic Switch - Page 2 of 2



Contact	Δd	justment	Tv	ne'
Contact	Au.	Justinent	ı y	ŊΦ.

External actuation point shaft with scale and external deactuation point shaft with scale

Contact Voltage Rating In Volts:

277.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A048b0