

View Online at <https://aerobasegroup.com/nsn/5930-01-157-2732>

Thread Class:

2b all threaded hole

Overall Length:

1.656 inches

Overall Height:

2.578 inches

Overall Width:

2.359 inches

Body Height:

2.422 inches

Distance Between Mounting Facility Centers:

1.750 inches

Capillary Tube Length:

24.0 inches

Bulb Length:

12.250 inches

Bulb Diameter:

0.188 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and threaded hole

Features Provided:

Capillary tube end seal connection

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

181.0 milliamperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.00/+700.00 actuation point degrees fahrenheit and +0.00/+700.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point shaft with scale and external deactuation point shaft with scale

Contact Voltage Rating In Volts:

277.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0