NSN 5930-01-157-4627

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-157-4627

Thread Length:
0.500 inches all threaded stud
Capillary Tube Length:
144.0 inches
Bulb Length:
4.468 inches
Bulb Diameter:
0.375 inches
End Application:
4920-01-040-2903
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Threaded stud
Thready Qty Per Inch (tpi):
32 all threaded stud
Contact Action Stimulus:
Decrease
Thread Size:
0.164 inches all threaded stud
Mounting Facility Pattern:
Two position in-line
Two position in-line Nonpile-up Contact Arrangement:
·
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Actuation point adjustable
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +50.00/+150.00 actuation point degrees fahrenheit
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +50.00/+150.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +50.00/+150.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 480.0 ac at sea level single voltage
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +50.00/+150.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 480.0 ac at sea level single voltage Media For Which Designed:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +50.00/+150.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 480.0 ac at sea level single voltage Media For Which Designed: Gas or liquid
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +50.00/+150.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 480.0 ac at sea level single voltage Media For Which Designed: Gas or liquid Thread Series Designator:
Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Wire lead Contact Load Current Rating: 3.0 amperes resistive load single voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +50.00/+150.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 480.0 ac at sea level single voltage Media For Which Designed: Gas or liquid Thread Series Designator: Unc all threaded stud

--

NSN 5930-01-157-4627

Thermostatic Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A048b0