

View Online at <https://aerobasegroup.com/nsn/5930-01-157-5763>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.997 inches and 1.003 inches

Overall Height:

1.237 inches

Overall Width:

0.755 inches

Body Width:

0.755 inches

Unthreaded Mounting Hole Diameter:

Between 0.140 inches and 0.144 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.687 inches

Actuator Roller Diameter:

Between 0.209 inches and 0.213 inches

Actuator Roller Width:

Between 0.154 inches and 0.158 inches

Maximum Voltage Rating In Volts:

110.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

48.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.040 pretravel inches and 0.125 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0