

View Online at <https://aerobasegroup.com/nsn/5930-01-157-7713>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Fungus resistant

Bushing Length:

0.470 inches

Body Length:

0.572 inches

Body Width:

0.354 inches

Actuator Length:

0.880 inches

Actuator Style:

Rectangular

Actuator Height:

0.460 inches

Actuator Width:

0.380 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0