

View Online at <https://aerobasegroup.com/nsn/5930-01-157-9585>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.473 inches

First Flat Length:

0.281 inches single actuator

Flat Height:

0.187 inches single actuator and 0.189 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.343 inches single actuator

Overall Diameter:

1.000 inches

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+0.750/+4.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0