NSN 5930-01-157-9639

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-157-9639

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant and shock resistant and vibration resistant

Overall Length:

0.480 inches

Overall Height:

1.830 inches

Overall Width:

1.610 inches

Distance Between Mounting Facility Centers:

1.385 inches single mounting facility

Individual Section Quantity:

1

Operating Tempurature Range:

-55.0/+71.0 degrees celsius

End Application:

5840-01-141-4378 radar set

Mounting Method:

Flange single mounting facility and threaded hole single mounting facility

Actuator Type:

Toggle single actuator

Features Provided:

Rfi shielding

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

6 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5 single section

Contact Arrangement Truth Table:

Bcd, separate common to not-true bits, 2 pole - 10 positions single section

NSN 5930-01-157-9639

Code Indicating Wheel Switch - Page 2 of 2



Special Features:
Stops provided to limit switch to 6 positions
Color:
White single indicator marking
Precious Material And Location:
Rfi shielding surfaces silver
Precious Material:
Silver
Style Designator:
Rectangular indicating
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0