

View Online at <https://aerobasegroup.com/nsn/5930-01-158-2240>

Hazardous Locations/environmental Protection:

Explosion proof and raintight

Overall Length:

5.438 inches

Overall Height:

3.500 inches

Overall Width:

4.375 inches

Unthreaded Mounting Hole Diameter:

0.266 inches

Distance Between Mounting Facility Centers:

4.875 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.15/+0.50 actuation point inches of water

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0