

View Online at <https://aerobasegroup.com/nsn/5930-01-158-2240>

**Hazardous Locations/environmental Protection:**

Explosion proof and raintight

**Overall Length:**

5.438 inches

**Overall Height:**

3.500 inches

**Overall Width:**

4.375 inches

**Unthreaded Mounting Hole Diameter:**

0.266 inches

**Distance Between Mounting Facility Centers:**

4.875 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -40.0 degrees fahrenheit and 140.0 degrees fahrenheit

**Mounting Method:**

Flange and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+0.15/+0.50 actuation point inches of water

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

480.0 ac at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/lugs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0