

View Online at <https://aerobasegroup.com/nsn/5930-01-158-2423>

Thread Class:

2b all threaded hole

Overall Length:

4.906 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

3.593 inches

Overall Diameter:

1.750 inches

Longest Horizontal Distance Between Mounting Centers:

1.082 inches

Shortest Horizontal Distance Between Mounting Centers:

0.540 inches

Longest Vertical Distance Between Mounting Centers:

0.937 inches

Temperature Sensing Element Type:

Expanding shell

Mounting Method:

Flange and threaded hole

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-100.00/+400.00 actuation point degrees fahrenheit and -100.00/+400.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

124.00 actuation point degrees fahrenheit and 119.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0