

View Online at <https://aerobasegroup.com/nsn/5930-01-158-4808>

Body Style:

Bushing mount

Bushing Length:

0.437 inches

Body Length:

1.330 inches

Body Width:

0.750 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

Between 1.035 inches and 1.129 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked out and down position no locking action and center position no locking action

Maximum Voltage Rating In Volts:

12.0 dc

End Application:

2320-01-123-6827

Mounting Surface To Terminal End Distance:

1.500 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 10.000 amperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0