

View Online at <https://aerobasegroup.com/nsn/5930-01-158-5609>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Shock resistant and waterproof

**Bushing Length:**

0.470 inches

**Body Length:**

0.860 inches

**Body Width:**

0.990 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

1.180 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position no locking action and center position locked in

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

F-4s acft

**Mounting Surface To Terminal End Distance:**

1.125 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded bushing

**Features Provided:**

Holding mechanism

**Nonpile-up Contact Arrangement:**

3 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive dc and 5.000 amperes inductive ac and 1.500 amperes lamp ac and 5.000 amperes resistive ac

**Terminal Type And Quantity:**

9 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0