

View Online at <https://aerobasegroup.com/nsn/5930-01-158-5609>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Shock resistant and waterproof

Bushing Length:

0.470 inches

Body Length:

0.860 inches

Body Width:

0.990 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

1.180 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

F-4s acft

Mounting Surface To Terminal End Distance:

1.125 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded bushing

Features Provided:

Holding mechanism

Nonpile-up Contact Arrangement:

3 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive dc and 5.000 amperes inductive ac and 1.500 amperes lamp ac and 5.000 amperes resistive ac

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0