NSN 5930-01-159-1629

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-159-1629 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Moisture resistant **Overall Length:** 0.840 inches **Overall Height: 2.732** inches **Overall Width:** 0.719 inches **Bushing Length:** 0.470 inches **Body Length:** 0.840 inches **Body Width:** 0.719 inches **Body Height:** 0.892 inches **Actuator Style:** Round **Actuator Diameter:** 0.428 inches **Actuator Height:** 1.180 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position maintained **Actuator Color:** White single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Mounting Surface To Terminal End Distance:** 1.082 inches **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

NSN 5930-01-159-1629

Toggle Switch - Page 2 of 2



١	lon	au-elic	Contact	Arrangem	ent:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes inductive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0