

View Online at <https://aerobasegroup.com/nsn/5930-01-159-2609>

**Body Style:**

Bushing mounted

**Bushing Length:**

0.375 inches

**Body Width:**

0.625 inches

**Body Height:**

1.375 inches

**Actuator Style:**

Round

**Actuator Height:**

0.859 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in and center position locked in

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**End Application:**

4920-01-066-4155

**Inclosure Type:**

Uninclosed

**Thready Qty Per Inch (tpi):**

32

**Pile-up Contact Form Arrangement:**

2k 2nd position

**Thread Size:**

0.469 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 3.000 amperes resistive ac

**Special Features:**

Non-turn device

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0