NSN 5930-01-159-3282

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-159-3282

| Body Style: | | | | |
|--|--|--|--|--|
| Bushing mount | | | | |
| Overall Length: | | | | |
| 0.700 inches | | | | |
| Overall Height: | | | | |
| 1.380 inches | | | | |
| Overall Width: | | | | |
| 0.510 inches | | | | |
| Bushing Length: | | | | |
| 0.320 inches | | | | |
| Body Length: | | | | |
| 0.700 inches | | | | |
| Body Width: | | | | |
| 0.510 inches | | | | |
| Body Height: | | | | |
| 0.490 inches | | | | |
| Case Material: | | | | |
| Plastic | | | | |
| Actuator Style: | | | | |
| Round | | | | |
| Actuator Diameter: | | | | |
| 0.120 inches | | | | |
| Actuator Height: | | | | |
| 0.410 inches | | | | |
| Actuator Position-action Relationship: | | | | |
| Up position maintained and down position maintained and center position maintained | | | | |
| Maximum Voltage Rating In Volts: | | | | |
| 250.0 ac and 28.0 dc | | | | |
| Mounting Surface To Terminal End Distance: | | | | |
| 0.650 inches | | | | |
| Inclosure Type: | | | | |
| Fully enclosed | | | | |
| Mounting Method: | | | | |
| Threaded bushing | | | | |
| Thready Qty Per Inch (tpi): | | | | |
| 40 | | | | |
| Thread Size: | | | | |
| 0.250 inches | | | | |
| Nonpile-up Contact Arrangement: | | | | |
| 3 pole, double throw, both positions maintained single switch unit | | | | |

4.000 amperes resistive dc and 3.000 amperes resistive ac

Contact Load Current Rating At Maximum Rated Voltage:

NSN 5930-01-159-3282

Toggle Switch - Page 2 of 2



| Precious | Material | And | Location: |
|----------|----------|-----|-----------|
|----------|----------|-----|-----------|

Terminal surfaces gold and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0