NSN 5930-01-159-5781

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-159-5781

Bady Style.
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
5.860 inches
Overall Height:
2.590 inches
Overall Width:
1.880 inches
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
1.780 inches
Housing Length:
4.690 inches
Housing Width:
1.880 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.340 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.160 inches
Maximum Voltage Rating In Volts:
600.0 ac and 240.0 dc
End Application:
Radar system an/fps-117
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Switch Actuating Force:
64.0 inch-ounces

Actuator Movement:

Between 15.0 pretravel degrees and 60.0 overtravel degrees and 7.0 differential degrees

NSN 5930-01-159-5781

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 150.000 milliamperes inductive dc and 600.000 milliamperes resistive ac

Special Features:

Two hole mounting

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0