

View Online at <https://aerobasegroup.com/nsn/5930-01-159-8066>

Overall Length:

8.562 inches

Outside Diameter:

0.250 inches single connection

Overall Height:

5.250 inches

Overall Width:

2.812 inches

Body Length:

5.250 inches

End Application:

Used on main reduction gear model hsq2724 onboard 210 wmec class b coast guard vessels

Pressure Switch Type:

Gage

Temperature Sensing Element Type:

Bulb

Mounting Method:

Immersion well

Cubic Measure:

432.000 cubic inches

Contact Action Stimulus:

Increase

Proof Pressure:

80.00 pounds per square inch

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable

Contact Adjustment Range:

+5.00/+25.00 actuation point pounds per square inch and +1.00/+20.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Stimulus Rating:

5.00 actuation point pounds per square inch and 185.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage

Pressure Connector Type:

Flared, threaded external single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A048b0