## NSN 5930-01-159-8927

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-159-8927

Panel mounted  Actuator Style: Rectangular  Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac  Inclosure Type: Fully enclosed  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 ampere inductive ac and 1.500 amperes lamp ac  Terminal Type And Quantity: 5 tab, solder lug and 12 turret  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	
inductive ac and 1.500 amperes lamp ac  Terminal Type And Quantity: 5 tab, solder lug and 12 turret  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	Body Style:
Rectangular  Maximum Voltage Rating In Volts: 28.0 dc and 115.0 ac  Inclosure Type: Fully enclosed  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 ampere inductive ac and 1.500 amperes lamp ac  Terminal Type And Quantity: 5 tab, solder lug and 12 turret  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Panel mounted
Maximum Voltage Rating In Volts:  28.0 dc and 115.0 ac  Inclosure Type:  Fully enclosed  Nonpile-up Contact Arrangement:  4 pole, double throw, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 ampere inductive ac and 1.500 amperes lamp ac  Terminal Type And Quantity:  5 tab, solder lug and 12 turret  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Actuator Style:
28.0 dc and 115.0 ac  Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 ampere inductive ac and 1.500 amperes lamp ac Terminal Type And Quantity: 5 tab, solder lug and 12 turret Shelf Life: N/a Unit Of Measure:	Rectangular
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 ampere inductive ac and 1.500 amperes lamp ac Terminal Type And Quantity: 5 tab, solder lug and 12 turret Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Maximum Voltage Rating In Volts:
Fully enclosed  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac  Terminal Type And Quantity: 5 tab, solder lug and 12 turret  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	28.0 dc and 115.0 ac
Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 ampere inductive ac and 1.500 amperes lamp ac Terminal Type And Quantity: 5 tab, solder lug and 12 turret Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Type:
4 pole, double throw, one position momentary single switch unit  Contact Load Current Rating At Maximum Rated Voltage:  5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 ampere inductive ac and 1.500 amperes lamp ac  Terminal Type And Quantity:  5 tab, solder lug and 12 turret  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Fully enclosed
Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac  Terminal Type And Quantity: 5 tab, solder lug and 12 turret  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Nonpile-up Contact Arrangement:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac  Terminal Type And Quantity: 5 tab, solder lug and 12 turret  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	4 pole, double throw, one position momentary single switch unit
inductive ac and 1.500 amperes lamp ac  Terminal Type And Quantity: 5 tab, solder lug and 12 turret  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	Contact Load Current Rating At Maximum Rated Voltage:
Terminal Type And Quantity: 5 tab, solder lug and 12 turret  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	inductive ac and 1.500 amperes lamp ac
Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Filig:	5 tab, solder lug and 12 turret
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Filg:	
Fiig:	Demilitarization:
	No
Δ053a0	Fiig:
10000	A053a0