

View Online at <https://aerobasegroup.com/nsn/5930-01-160-0102>

**Body Style:**

Bushing mounted

**Body Diameter:**

0.562 inches

**Bushing Length:**

Between 0.415 inches and 0.435 inches

**Body Length:**

1.020 inches

**Actuator Diameter:**

0.500 inches

**Actuator Height:**

Between 0.485 inches and 0.525 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Green single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Receiving set, countermeasures an/slr-16

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug and 3 turret

**Specification Data:**

81349-mil-s-22885/79 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0