NSN 5930-01-160-0104

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-160-0104

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
2.751 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.688 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.090 inches
Actuator Width:
0.620 inches
Actuator Color:
Natural single actuator
Illuminated Actuator Color:
Natural single actuator
Actuator Inscription:
Rcvr asgn single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Direction finder set an/brd-8
Mounting Surface To Terminal End Distance:
2.688 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonnile-un Contact Arrangement

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-160-0104

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0