NSN 5930-01-160-0108

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mounted

Explosion proof



View Online at https://aerobasegroup.com/nsn/5930-01-160-0108

Overall Length:					
2.851 inches					
Overall Height:					
0.750 inches					
Overall Width:					
0.750 inches					
Body Width:					
0.750 inches					
Body Height:					
0.688 inches					
Case Material:					
Metal					
Actuator Length:					
0.620 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
0.090 inches					
Actuator Width:					
0.620 inches					
Actuator Color:					
Natural single actuator and green single actuator					
Illuminated Actuator Color:					
Natural single actuator and green single actuator					
Actuator Inscription:					
Hf-3 single actuator					
Illuminated Actuator Color Sequence:					
Upper half of actuator clear lower half of actuator green					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
End Application:					
Direction finder set an/brd-8					
Mounting Surface To Terminal End Distance:					
2.688 inches					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					

NSN 5930-01-160-0108

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

_		B4 - 4 -	!	AI	
М	recious	wate	eriai	Ana	Location:

Contacts silver

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0